

(12) **United States Patent**
Kraenzler et al.

(10) **Patent No.:** **US 8,522,894 B2**
(45) **Date of Patent:** **Sep. 3, 2013**

(54) **HAND MACHINE TOOL COMPRISING AT LEAST ONE HANDLE**

(75) Inventors: **Ernst Kraenzler**, Leinfelden-Echterdingen (DE); **Manfred Ruff**, Stuttgart (DE); **Harald Krondorfer**, Ludwigsburg (DE); **Ralph Dammertz**, Stuttgart (DE); **Joerg Goehner**, Boeblingen-Dagersheim (DE); **Mario Frank**, Remshalden (DE); **Franz Scheschark**, Neuenstadt (DE)

(73) Assignee: **Robert Bosch GmbH**, Stuttgart (DE)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 1930 days.

(21) Appl. No.: **10/049,546**

(22) PCT Filed: **May 25, 2001**
(Under 37 CFR 1.47)

(86) PCT No.: **PCT/DE01/02024**
§ 371 (c)(1),
(2), (4) Date: **Jun. 5, 2003**

(87) PCT Pub. No.: **WO03/043785**
PCT Pub. Date: **May 30, 2003**

(65) **Prior Publication Data**
US 2005/0224244 A1 Oct. 13, 2005

(30) **Foreign Application Priority Data**
Jun. 15, 2000 (DE) 100 29 536

(51) **Int. Cl.**
B25D 17/24 (2006.01)

(52) **U.S. Cl.**
USPC 173/162.1; 173/162.2

(58) **Field of Classification Search**
USPC 173/162.1, 162.2, 211, 136.1, 162, 173/136; 30/381, 382, 383, 384
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,683,334 A 9/1928 Chilton
3,728,793 A * 4/1973 Makinson et al. 30/383
4,603,904 A 8/1986 Tolleson et al.

(Continued)

FOREIGN PATENT DOCUMENTS

DE 1 103 773 3/1961
DE 1 628 926 9/1971

(Continued)

OTHER PUBLICATIONS

"Kunststoff-Lexikon" Carl Hanser Verlag Muenchen 1973, p. 375
(With Certified English Translation).


Primary Examiner — Rinaldi Rada
Assistant Examiner — Nathaniel Chukwurah
(74) *Attorney, Agent, or Firm* — Michael J. Striker

(57) **ABSTRACT**

The invention is based on a power tool with at least one handle (10, 26, 50, 62, 104) that comprises at least one grip part (12, 72, 106) that is firmly connected to a mounting part (16, 70, 110) via at least one elastic, vibration-damping element (14, 24, 52, 108), via which the grip part (12, 72, 106) is affixable to a housing (60).

It is proposed that the connection between the grip part (12, 72, 106) and the mounting part (16, 70, 110) is secured by means of the elastic element (14, 24, 52, 108) via at least one movable retaining element (20, 22, 28, 64, 112).

20 Claims, 8 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

4,995,598 A 2/1991 Ingham
 5,046,566 A * 9/1991 Dörner et al. 173/162.2
 5,052,500 A * 10/1991 Ohtsu 173/162.2
 5,157,807 A 10/1992 Keller et al.
 5,453,577 A * 9/1995 Everett et al. 173/211
 5,697,456 A 12/1997 Radle
 5,699,865 A * 12/1997 Forderer et al. 173/162.2
 6,412,180 B1 * 7/2002 Wolf et al. 30/381
 7,126,366 B2 10/2006 Ohashi et al.
 7,332,926 B2 2/2008 Ohashi et al.
 7,740,087 B2 6/2010 Krondorfer et al.

FOREIGN PATENT DOCUMENTS

DE 28 04 223 A 8/1979
 DE 81 19 172.3 11/1981
 DE 32 25 815 12/1983

DE 87 01 722.9 4/1987
 DE 87 01 722.9 5/1987
 DE 40 11 124 10/1991
 DE 41 24 574 1/1993
 DE 195 30 712 2/1997
 DE 195 30 712 A 2/1997
 DE 199 55 931 A 2/2001
 DE 100 05 080 8/2001
 EP 0 213 089 3/1987
 EP 0 336 627 10/1989
 EP 0 995 553 4/2000
 GB 586 608 3/1947
 JP 53-127256 11/1978
 JP 56163839 12/1981
 JP 06124183 5/1994
 JP 4628096 2/2011
 JP 4628421 2/2011

* cited by examiner




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9




Fig. 10




Fig. 11




Fig. 12

1

HAND MACHINE TOOL COMPRISING AT LEAST ONE HANDLE

RELATED ART

The invention is based on a power tool with at least one handle according to the preamble of claim 1.

A handle for guiding or holding vibrating devices was made known in DE 87 01 722.9 C1. The handle comprises a grip part having a metal core coated with a vibration-damping plastic. A first piece of sheet metal is connected to the metal core on one end via a screw, which first piece of sheet metal is connected to a second piece of sheet metal via an elastic buffer in the axial direction opposite to the grip part. The second piece of sheet metal, in turn, is connected to a guide shaft of the device via a screw.

ADVANTAGES OF THE INVENTION

The invention is based on a power tool with at least one handle that comprises at least one grip part that is firmly connected to a mounting part via at least one elastic, vibration-damping element, via which the grip part is affixable to a housing.

It is proposed that a connection between the grip part and the mounting part is secured using the elastic element via at least one movable retaining element. If the elastic element becomes damaged, the grip part can be prevented from separating from the housing, and control of the power tool via the grip part can be ensured at all times. Transmission of vibrations via the retaining element can be prevented by means of the movable design of the retaining element when [the power tool is] operated properly. The mounting part is advantageously designed as a piece separate from the housing, although it can also be designed at least partially integrated with the housing of the power tool.

In a further embodiment, however, it is proposed that the retaining element is formed by a flexible element, e.g., by a chain or, advantageously, by a plastic or wire rope, etc. When a flexible retaining element is used, a transmission of vibrations can be prevented cost-effectively using a simple design, and the retaining element can be favorably integrated in the elastic element.

In order to protect the retaining element from damage during operation of the power tool, and to make a concealed integration of the retaining element in the handle possible, the elastic element advantageously encloses the retaining element.

It is further proposed that the retaining element is located in the elastic element in the center along a centerline, by way of which, when a tilting motion takes place, undesired tensile stresses in the retaining element and a transmission of vibration associated therewith can be prevented.

If the retaining element, in the installed state, is subjected to compressive stresses, and the elastic element is subjected to tensile stresses, a higher loadability of the elastic element can be achieved than without pretension, and breakage or separation from the grip part and from the mounting part and/or a tearing of the elastic element can be prevented. Moreover, the retaining element can be used advantageously to secure the elastic element to the grip part and to the mounting part, e.g., in that the retaining element applies a contact force necessary for a cemented joint. The compressive stress can be advantageously achieved in the elastic element by tensioning the retaining element, e.g., by tensioning a flexible retaining element—advantageously located in the middle of the elastic element along a centerline—using a fastening screw.

2

In a further embodiment according to the invention, it is proposed that the retaining element is formed by a band that encloses the elastic element. The retaining element designed in the shape of a band can protect the elastic element—formed out of a usually soft material—against outside influences and damage during operation, e.g., against heat, effects of ultraviolet radiation, dust, moisture, and hard objects, etc., by means of its closed surface. The band can be produced out of various materials appearing reasonable to one skilled in the art, e.g., out of fabric tape, etc. Basically, the retaining element can also be formed cost-effectively out of at least one flexible component that is located radially outside of the elastic element, e.g., out of one or more ropes.

In order to protect the elastic element from outside influences, it can also be enclosed in a sleeve made of solid material, which sleeve can be secured to the grip part or the mounting part and is located at a distance from the grip part or the mounting part in order to prevent transmission of vibrations.

The retaining element can be formed out of a rigid component instead of a flexible component, which rigid component is supported in movable fashion relative to the mounting part and/or the grip part. The retaining element can be designed to be easily installed or removed, so it can be replaced if damaged. Moreover, a maximum displacement of the elastic element from a normal position can be easily determined in at least one tilting direction and/or one sliding direction via the retaining element and, in particular, via a rigid retaining element. An overstretching of the elastic element can be prevented by means of the retaining element, and a long service life can be achieved.

The retaining element is advantageously supported firmly in the mounting part and in movable fashion relative to the grip part, whereby a space in the grip part can advantageously be used for a freedom of motion of the retaining element and a simple installation starting with the grip part can be achieved. Moreover, a fastening screw located in the mounting part can be used for a firm connection of the retaining element. Additional mounting parts for the retaining element can be spared. Basically, however, the retaining element can also be designed to be rigid in the grip part and movable in relation to the mounting part.

It is further proposed that the retaining element is formed by a screw that can be screwed particularly advantageously into the fastening screw in the mounting part. A screw is particularly cost-effective and can be installed and removed particularly easily and quickly. Instead of a screw, however, a bolt could be used that can be secured either in the grip part or in the mounting part in positive, non-positive, and/or bonded fashion, e.g., it can be pressed in the fastening screw in the mounting part.

In addition to a rigid bar, a screw, a chain, and a rope, furthermore, a spring can be used as the retaining element, in particular a coiled spring. Using a fastening element formed by a coiled spring, a particularly simple installation can be achieved, particularly in automated series production.

In order to make an advantageous uniform cooling, and advantageously homogenous microstructure, and an advantageously bonded connection to the mounting part and/or the grip part possible after injection molding of the elastic element, the elastic element comprises a non-circular cross-sectional area at least closely before an advantageously round seating surface with the mounting element and/or with the grip part that is smaller than the seating surface, and, in fact, the cross-sectional area is composed particularly advantageously of a round core area and arched extensions abutting the core area radially on the outside. Using a round contour,

an advantageously large seating surface between the elastic element and the mounting part and the grip part can be achieved. The seating region can be cooled advantageously by means of the smaller cross-sectional area abutting this.

Moreover, an advantageous microstructure can be enhanced by dissipating heat from an internal region of the elastic element via at least one component during production of the elastic element. The component can be formed by means of a retaining element inserted in the elastic element during production itself, or advantageously by a core that is removed after the elastic element is manufactured, and advantageously forms a recess for the retaining element. Advantageously, the core can be cooled compared to the inserted retaining element using a coolant by means of a cooling passage. When using retaining elements in particular that are formed out of rigid components and that can be installed easily after production of the elastic element, it is advantageous that the elastic element can be cooled by means of a core during production.

The means of attaining the object of the invention can be used with various power tools appearing practical to one skilled in the art, e.g., with hammer drills, rotary hammers, drills, power-operated screw drivers, sawing, milling, planing, etc. The means of attaining the object of the invention according to the invention can be used with particular advantage in angle grinders, however, and, in fact, using an additional handle extending transversely to the longitudinal direction, which serves primarily to guide the angle grinder.

BRIEF DESCRIPTION OF THE DRAWING

Further advantages arise from the following drawing description. Exemplary embodiments of the invention are presented in the drawing. The drawing, the description, and the claims contain numerous features in combination. One skilled in the art will advantageously consider them individually as well and combine them into reasonable further combinations.

FIG. 1 shows a schematic representation of an angle grinder from above,

FIG. 2 shows a handle according to the invention comprising a flexible retaining element enclosed in an elastic element,

FIG. 3 shows a handle with a retaining element designed in the shape of a rod,

FIG. 4 shows a section of an alternative to FIG. 3,

FIG. 5 shows a view along the line V-V in FIG. 4 during assembly,

FIG. 6 shows a handle comprising an elastic element enclosed by a retaining element designed in the shape of a band,

FIG. 7 shows a variant of FIG. 3,

FIG. 8 shows a view along the line VIII-VIII in FIG. 7,

FIG. 9 shows a view along the line IX-IX in FIG. 7,

FIG. 10 shows a view along the line X-X in FIG. 7,

FIG. 11 shows a view along the line XI-XI in FIG. 7, and

FIG. 12 shows a handle according to FIG. 7 during its production.

DETAILED DESCRIPTION OF THE EXEMPLARY EMBODIMENT

FIG. 1 shows an angle grinder having an electric motor (not shown) supported in a housing 56, via which a cutoff wheel clamped in the toolholder is driveable. The angle grinder is guidable via a first handle 58 integrated in the housing 56 on the side opposite to the cutoff wheel 54 and extending in the longitudinal direction, and via a second handle 10 secured to

a gearbox housing 60 in the region of the cutoff wheel 54 or the toolholder and extending transversely to the longitudinal direction. The handle 10 comprises a grip part 12 that is firmly connected via an elastic, vibration-damping plastic element 14 to a mounting part 16, via which the grip part 12 is secured to the gearbox housing 60 of the angle grinder via a set screw 18 integrally molded to the mounting part 16. The elastic plastic element 14 is integrally extruded on the grip part 12 and the mounting part 16 and, as a result, is firmly connected to them.

According to the invention, the grip part 12, in addition to the elastic plastic element 14, is connected to the mounting part 16 via a movable retaining element 20 (FIG. 2). The retaining element 20 is formed by a flexible component in the form of a wire rope and is located in the elastic plastic element 14 along a centerline. Threaded sleeves (not shown) are secured to the ends of the retaining element 20, via which the retaining element 20 is screwed to the grip part 12 and the mounting part 16. The elastic plastic element 14 encloses the retaining element 20. The retaining element 20, in the installed state, is subjected to tensile stresses, and the elastic element 14 is subjected to compressive stresses.

FIG. 3 shows a further embodiment of a handle 26 according to the invention, in which a retaining element 22 is formed by a rigid rod supported in movable fashion and enclosed in an elastic plastic element 24 applied by injection molding, to the ends of which washers 30, 32 are secured in each case. Components that are essentially identical are labelled with the same reference numerals in the exemplary embodiments presented. With regard for features and functions that remain the same, reference is made to the description of FIG. 1.

One sleeve 34, 36 each is secured to the mounting part 16 and the grip part 12, each of which comprises a washer 38, 40 having coaxial openings 42, 44 in the direction toward the elastic plastic element 24. The sleeves 34, 36 and the washers 38, 40 each abut a space 46, 48 filled via injection with an elastic material, into which the retaining element 22 with its washers 30, 32 is inserted. The washers 30, 32 of the retaining element 22 have a larger diameter than the openings 42, 44 and are held captive in the spaces 46, 48.

For installation, the washer 30 can be unscrewed from the rod-shaped part of the retaining element 22. The retaining element 22 can then be inserted into this—before installation of the sleeves 34, 36 with the grip part 12 or the mounting part 16—and the washer 30 can be screwed to the rod-shaped part once more. The sleeves 34, 36 are connected to the grip part 12 or the mounting part 16 via threaded joints (not shown). After the sleeves 34, 36 are connected to the grip part 12 and the mounting part 16, the retaining element 22 is coated with elastic plastic applied by injection molding.

The sleeves 34, 36, with their washers 38, 40, advantageously produce a positive connection between the grip part 12 and the elastic plastic element 24, and between the elastic plastic element 24 and the mounting part 16. Basically, however, the elastic plastic element could be designed with the retaining element, the sleeves, and the washers as an assembly capable of being preassembled, which is then screwed and cemented to the grip part and the mounting part.

A maximum displacement of the elastic plastic element 24 is determined by a freedom of motion of the washers 30, 32 of the retaining element 22 in the spaces 46, 48, in all directions, in fact. In order to prevent a transmission of vibrations via the retaining element 22, the retaining element 22 is situated at a distance—filled with an elastic material—from the sleeves 34, 36 and the washers 38, 40 when [the power tool] is operated properly.

5

A further exemplary embodiment of a handle **62** is shown in FIGS. **4** and **5**, in which a retaining element **64** is formed by a rigid rod supported in movable fashion and comprising a coating of an elastic plastic element **24** applied by injection molding, the ends **66**, **68** of which are designed in the shapes of washers. With regard for features and functions that remain the same, reference is made to the description of FIG. **3**.

One structural part **74**, **76** each is integrally molded to a mounting part **70** and a grip part **72**, each of which is designed in the shape of a washer in the direction toward the elastic plastic element **24** and which comprise coaxial openings **78**, **80**.

The structural parts **74**, **76** each abut a space **82**, **84** filled with an elastic material applied by injection, into which the retaining element **64**—designed as a single piece—is inserted with its washer-shaped ends **66**, **68** during assembly. The retaining element **64** with its rod-shaped part is thereby guided transverse to the longitudinal direction of the handle **62** through lateral openings **86**, **88** in the structural parts **74**, **76** (FIG. **5**). The retaining element **64** is then secured in the structural parts **74**, **76** against the direction of its insertion **90** by means of the openings **86**, **88** by pushing structural parts **92**, **94**—each of which has an L-shape in the longitudinal view—perpendicular to the direction of insertion **90** and transverse to the longitudinal direction with one opening **96**, **98** each over the rod-shaped part of the retaining element **64**. The rod-shaped ends **66**, **68** of the retaining element **64** have a greater diameter than the openings **78**, **80** and are held captive in the spaces **82**, **84**. The retaining element **64** is then coated with plastic applied by injection molding.

A width **100** of the openings **86**, **88** transverse to the longitudinal direction of the handle **62** and perpendicular to the direction of insertion **90** of the retaining element **64** is advantageously designed smaller than a diameter **102** of the rod-shaped part of the retaining element **64**, so that the retaining element **64** must be pushed through the openings **86**, **88** against resistance and then locks in place in the openings **78**, **80** of the structural parts **74**, **76**. The retaining element **64** is secured in the openings **78**, **80** of the structural parts **74**, **76**, and the structural parts **92**, **94** can be advantageously spared.

FIG. **6** shows a further exemplary embodiment of a handle **50** in which, according to the invention, a retaining element **28** is formed by a flexible fabric tape that encloses an elastic plastic element **52**. The band-shaped retaining element **28** is designed to be essentially non-elastic in the longitudinal direction of the handle **50** and comprises a plastic flange (not shown) abutting the grip part **12** and abutting the mounting part **16** in each case, with which the band-shaped retaining element **28** is firmly connected to the grip part **12** or with the mounting part **16** via arresting connections.

In order to prevent a transmission of vibrations via the retaining element **28**, it is designed longer than the elastic plastic element **52**. The elastic plastic element **52** is protected by the retention element **28** against outside influences and damage while the angle grinder is in use. Moreover, a maximum displacement of the elastic plastic element **52** from its normal position is determined by the retention element **28** and, in fact, in the directions of push, tilt, and pull. In the maximum displacement positions, the retention element **28** is tensioned and prevents a further displacement of the elastic plastic element **52**.

A handle **104** that is an alternative to the exemplary embodiment in FIG. **3** is shown in FIGS. **7** through **12**. The handle **104** comprises a mounting part **110** that is firmly connected via an elastic plastic element **108** with a grip part

6

106. The connection between the mounting part **110** and the grip part **106** is secured via a retention element **112** formed by a screw (FIG. **8**).

During production of the handle **104**, the mounting part **110** and the grip part **106** are first produced out of plastic via injection molding, and a fastening screw **114** is inserted in the mounting part **110** and coated via injection molding with positive engagement in the axial direction and in the direction of rotation, which fastening screw **114** comprises an external thread **118** as well as an internal thread **120** for fastening to a machine housing in the direction of the grip part **106**. The fastening screw **114** could also be pressed into a mounting part afterwards. After applying a coating to the fastening screw **114** via injection molding, the mounting part **110** with the fastening screw **114** and the grip part **106** are placed in a casting mold **140** in order to become bonded to the elastic plastic element **108** in an injection molding procedure (FIG. **12**). The casting mold **140** is shaped so that the elastic plastic element **108** comprises a non-circular cross-sectional area **116** closely before a round seating surface **146** with the mounting part **110** and a round seating surface **134** with the grip part **106**, each of which is smaller than the seating surfaces **134**, **146** and, in fact, the cross-sectional areas **116** each comprises a round core area **122** abutted radially on the outside by four arched extensions **124**, **126**, **128**, **130** (FIGS. **9** and **11**). More or fewer than four arched extensions **124**, **126**, **128**, **130** would also be possible. The elastic plastic element **108** comprises a round cross-sectional area **136** in a center region (FIG. **10**).

Moreover, a core **142** cooled via a fluid passage **148** is placed in the casting mold **140** that forms a recess **144** for the retention element **112**, via which core **142** heat is dissipated from the interior region of the elastic plastic element **108** during production. The grip part **106** is designed hollow inside and comprises a recess **138** in the direction of the mounting part **110** through which the core **142** extends, and which is partially filled with the elastic plastic element **108** applied via injection, so that a flange **150** of the elastic plastic element **108** grips behind an edge region of the recess **138**.

Once the elastic plastic element **108** has cooled and the core **142** has been removed, the retention element **112** of the grip part **106** is guided through the recess **144** formed by the core **142** in the direction of the mounting part **110** through the elastic plastic element **108** and is screwed into the interior thread **120** in the fastening screw **114**. The retention element **112** comprises a screw head **132** that, when the retention element **112** is installed, is situated at a distance from the grip part **106**, so that the retention element **112** is supported in movable fashion relative to the grip part **106**. The screw head **132** is larger than the recesses **138** and **144**, so that, if the elastic plastic element **108** becomes damaged, the grip part **106** is connected to the mounted part **110** in captive fashion. The distance between the screw head **132** and the grip part **106** determines a maximum permissible displacement of the elastic plastic element **108**. Direct contact between the screw head **132** and the grip part **106** is prevented and transmission of vibrations is largely prevented by means of the flange **150** when maximum displacement occurs.

REFERENCE NUMERALS

10 handle
12 grip part
14 element
16 mounting part
18 set screw
20 retaining element

22 retaining element
 24 element
 26 handle
 28 retaining element
 30 washer
 32 washer
 34 sleeve
 36 sleeve
 38 washer
 40 washer
 42 opening
 44 opening
 46 space
 48 space
 50 handle
 52 element
 54 cutoff wheel
 56 housing
 58 handle
 60 gearbox housing
 62 handle
 64 retaining element
 66 end
 68 end
 70 mounting part
 72 grip part
 74 structural part
 76 structural part
 78 opening
 80 opening
 82 space
 84 space
 86 opening
 88 opening
 90 direction of insertion
 92 structural part
 94 structural part
 96 opening
 98 opening
 100 width
 102 diameter
 104 handle
 106 grip part
 108 element
 110 mounting part
 112 retaining element
 114 fastening screw
 116 cross-sectional area
 118 external thread
 120 internal thread
 122 core area
 124 extension
 126 extension
 128 extension
 130 extension
 132 screw head
 134 seating surface
 136 cross-sectional area
 138 recess
 140 casting mold
 142 component
 144 recess
 146 seating surface
 148 fluid passage
 150 flange

What is claimed is:

1. A power tool with at least one handle, said handle comprising at least one grip part that is firmly connected to and firmly held at a mounting part by at least one elastic, vibration-damping element, wherein the grip part is affixed to a housing via the mounting part, and
 - wherein the connection between the grip part and the mounting part by means of the elastic element is secured by at least one movable retaining element, wherein the retaining element is formed by a flexible component, wherein the retaining element is formed by a rope.
2. A power tool with at least one handle, said handle comprising at least one grip part that is firmly connected to and firmly held at a mounting part by at least one elastic, vibration-damping element located between the grip part and the mounting part, wherein the grip part is affixed to a housing via the mounting part which is screwed into the housing so that the elastic element is mounted to the housing through the mounting part and also mounted to the grip part; and wherein the connection between the grip part and the mounting part by means of the elastic element is secured by at least one movable retaining element that prevents a separation of the grip part from the housing if the elastic element is damaged and ensures control of the power tool via the grip part at all times.
3. The power tool according to claim 2, wherein the retaining element is formed by a flexible component.
4. The power tool according to claim 2, wherein the retaining element is located in the elastic element along a centerline.
5. The power tool according to claim 2, wherein the retaining element, in the installed state, is subjected to tensile stresses, and the elastic element is subjected to compressive stresses.
6. The power tool according to claim 2, wherein the retaining element is formed by a band that encloses the elastic element.
7. The power tool according to claim 6, wherein a maximum displacement of the elastic element is determined by means of the retaining element in at least one tilting direction.
8. The power tool according to claim 2, wherein the retaining element is formed by a rigid component that is supported in movable fashion relative to the mounting part.
9. The power tool according to claim 8, wherein the retaining element is formed by a rigid component and is firmly supported in the mounting part and movable relative to the grip part.
10. The power tool according to claim 9, wherein the retaining element is firmly connected to a fastening screw located in the mounting part.
11. The power tool according to claim 9, wherein the retaining element is formed by a screw.
12. The power tool according to claim 8, wherein the retaining element is connected to the grip part via the elastic element and to the mounting part via the elastic element.
13. The power tool according to claim 2, wherein the elastic element comprises a non-circular cross-sectional area at least closely before a seating surface of the elastic element for at least one element, the element being an element selected from the group consisting of the mounting element and the grip part, wherein the cross-sectional area is smaller than the seating surface.
14. The power tool according to claim 2, wherein the elastic element encloses the retaining element.

15. The power tool according to claim 2, wherein the grip part comprises a recess, in which the retaining element is located.

16. The power tool according to claim 15, wherein the recess is partially filled with the elastic element. 5

17. The power tool according to claim 15, wherein the retaining element is formed by a screw having a screw head which is larger than the recess.

18. The power tool according to claim 17, wherein the elastic element has a flange preventing a direct contact 10 between the screw head and the grip part.

19. The power tool according to claim 15, wherein the elastic element has a flange gripping behind an edge region of the recess.

20. The power tool according to claim 2, wherein by the 15 retaining element the grip part is connected to the mounting part in captive fashion.

* * * * *